

SPECIFICATION



Tatton Slimline 10W & 20W

LED Floodlight



Beam Angle
110°



Input
200-240V



Life Hours
25,000



Dimmable
No



Colour Temperature
6000K

Without PIR (IP65)	TA1-10C	TA1-20C
With PIR (IP44)	TA1-10CP	TA1-20CP
Wattage	10W	20W
Input Voltage	200-240V	200-240V
Beam Angle	110°	110°
Life Expectancy	25,000	25,000
Colour Temperature	6000K	6000K
Output Lumens	775lm	1525lm
Dimmable	No	No
Switch Time	12500	12500
Instant Light	Yes	Yes
CRI	>80	>80
Dimensions without PIR (mm)	104 x 125 x 27	125 x 152 x 28
Dimensions with PIR (mm)	104 x 165 x 55	125 x 189 x 55

Key Features

- PIR with 4th wire override or slave function
- Angled bracket for easy installation
- Supplied with 1m cable
- 2 year warranty

CRI >80 **IP 65** **IP 44**

Please Note: Product specifications are subject to change without notice. Product supplied may differ slightly in appearance from images shown on this website. Diamond LED Lighting reserve the right to update product specifications

Tel: 01260 292 640 | Fax: 01260 279 116 | E-mail: sales@diamondledlighting.co.uk | Web: www.diamondledlighting.co.uk