

Solista LX Ceiling VAD

Part No. **BF441C/F/3**



Overview

Certified to EN54 Parts 23 (AFNOR) and 13(BSI).

Provides C-3-7.5 coverage (switchable to C-3-2.5 if required).

10-25mA alarm current depending on setting.

Attractive slim design.

Ultra-bright red LED.

Ideal for use in bedrooms, bathrooms and toilets.

Technical Specifications

Approvals/certifications	Certified to EN54-23 by AFNOR and EN54-13 by the BSI.
Protocol/compatibility	Can be used on the conventional sounder circuits of most conventional fire panels including C-TEC's FP, MFP, CFP & EP203. Can also be used on the conventional sounder circuits provided on CTEC's XFP and ZFP addressable panels.
Application/operation	Designed to be ceiling mounted. Indoor areas only.
VAD category & coverage	C-3-7.5 (switchable to C-3-2.5, reducing power consumption by up to 50%).
Flash rate & colour	1Hz (switchable to 0.5Hz) / red.
Supply/operating voltage	9-60V DC.
Quiescent current	TBC.
Alarm current	10-25mA dependent on setting.
Product dimensions (mm)	93mm diameter x 38mm deep.
Construction & finish	ABS FR & polycarbonate.
IP Rating	IP33C.
Weight	100g.
Operating conditions/temperature	-25°C to +70°C.



T 01942 322744 E sales@c-tec.co.uk
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom



T 01942 322744 E sales@c-tec.co.uk
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom